

UNIQ[®]VIS 886S

Solvent base conductive agent

UNIQ[®]VIS 886S is predominately recommended to solvent base system, can increase coating conductivity. No halogen, with excellent conducting performance by reducing electric resistance of coating and has good compatibility with wide range of binder systems, suited to be applied in low polarity to high polarity systems, good property stability at low temperature. No negative effect to coating properties including interlayer adhesion, yellowing, viscosity stability.

Special Features

- Predominately recommended to solvent base system
- Increase coating conductivity (by reducing electric resistance)
- Good stability at low temperature
- No halogen
- No negative effect to coating properties

Application

Architectural coatings	<input type="checkbox"/>
Wood and furniture coatings	<input checked="" type="checkbox"/>
Automotive and refinish coatings	<input checked="" type="checkbox"/>
Can/coil coatings	<input checked="" type="checkbox"/>
General Industrial coatings	<input checked="" type="checkbox"/>
Protective coatings	<input type="checkbox"/>

highly recommended
recommended

Product Specification

Active ingredients	60%
Solvent	Isobutanolðanol
Density 20 °C	0.983g/cm ³
Appearance	Yellow clear liquid
Color	Max.8

Addition levels

- In non-polar systems containing petroleum only solvents, it is recommended to premix with butanol in a 1:1 or 1:2 ratio to improve solubility and distribution, thereby improving conductivity.
- Based on formula weight 0.1-2%
- Can be added in the final stage of production.

Packaging

- 25 kg
- 190 kg

Shelf life

UNIQ[®]VIS 886S should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture.