UNIQ® JET 9557

Polymeric dispersing agent

is a polymeric dispersant which will improve pigment dispersion and stability in solvent based, solvent free and UV based coatings and inks. Specially suited for silica matting agents to offer low viscosity, high matting efficiency and transparency.

COMPOSITION

Solution of polymeric dispersant

PRODUCT SPECIFICATIONS

Active content	50%
Solvent	PMA
Density	1.0 g/cm^3
Amine value	24 mg KOH/g
Acid value	10 mg KOH/g
Colour	Max. 6
Appearance	Brownish clear liquid



SPECIAL FEATURES AND BENEFITS

High Efficiency
- Very suited for matting agents
- Suited for organic pigments
- Excellent compatibility
- Improved particle size reduction
- Improvements in particle size stability
- Excellent viscosity reduction and stability
- Good transparency and less haze

Suited for all pigments
- Suited for single grinding
- Suited for resin minimal pigment concentrates

APPLICATIONS

Wood and furniture coatings
Marine and protective coatings
Can and coil systems
Pigment concentrates
UV applications

ADDITION LEVELS

For the best performances the additive should be incorporated into the millbase before addition of the pigments. Amount of active additive based on pigment (SOP) recommendations:

Inorganic pigments	Matting agents	Organic pigments	Carbon black
2 – 5%	5 – 10%	15 – 40%	20 – 80%

Above recommended levels can be used for orientation and needs to be optimized by testing.

STORAGE, SAFETY AND PACKAGING

The product should be stored in a cool dry place above 5 °C. The performance is not impacted at lower temperature, but re-heating and mixing before use is recommended. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture.

The product is available in 25 kg pail and 190 kg drum.

UNIQCHEM (UK) CO., LTD

www.uniqchem.com
Info@uniqchem.com

Regional headquarters

UNIQ®FOAM, UNIQ®FLOW, UNIQ®WET, UNIQ®SPERSE, UNIQ®LIGHT, UNIQ®COLOR, UNIQ®MICA, UNIQ®CURE, UNIQ®JET, UNIQ®WAX, UNIQ®VIS
This information is given to the best of our knowledge and should only regard as recommendations. Because of the multitude of formulations, production and application conditions, all the above-mentioned statements have to be adjusted to the circumstances of the processor.
No liabilities, including those for patent rights, can be derived from this fact for individual cases.
This datasheet replaces all previous issues – Printed in UK
© Copyright UNIQCHEM (UK) CO., LTD.

Asia: UNIQCHEM Shanghai Co., Ltd. Tel: +86 21 5433 6480 asia@uniqchem.com
EMEA: UNIQCHEM GmbH Tel: +49 2862 587 9510 eu@uniqchem.com